

▼ シリンダスピード mm/秒 (計算値50Hz)

※効率100%と仮定した場合です。60Hzの場合は2割アップになります。

エナパック シリンダ クラス kN	シリンダ 受圧面積 cm ²	ポンプ・シリーズ (吐出量ℓ/分)									
		600 シリーズ		2000 シリーズ		3000 シリーズ		5000 シリーズ		6100 シリーズ	
		低圧	高圧	低圧	高圧	低圧	高圧	低圧	高圧	低圧	高圧
		3.2	0.32	6.2	0.55	8.9	0.82	11.6	1.64	18	2.5
RC-タイプ											
45kN	6.4	83.3	8.3	161.5	14.3	231.8	21.4	302.1	42.7	—	—
100kN	14.4	37.0	3.7	71.8	6.4	103.0	9.5	134.3	19.0	—	—
142kN	20.3	26.3	2.6	50.9	4.5	73.1	6.7	95.2	13.5	147.8	20.5
233kN	33.3	16.0	1.6	31.0	2.8	44.5	4.1	58.1	8.2	90.1	12.5
293kN	41.9	12.7	1.3	24.7	2.2	35.4	3.3	46.1	6.5	71.6	9.9
500kN	71.2	7.5	0.7	14.5	1.3	20.8	1.9	27.2	3.8	42.1	5.9
718kN	102.6	5.2	0.5	10.1	0.9	14.5	1.3	18.8	2.7	29.2	4.1
933kN	133.1	4.0	0.4	7.8	0.7	11.1	1.0	14.5	2.1	22.5	3.1
RCH-タイプ											
125kN	17.8	30.0	3.0	58.1	5.1	83.3	7.7	108.6	15.4	168.5	23.4
214kN	30.3	17.6	1.8	34.1	3.0	49.0	4.5	63.8	9.0	99.0	13.8
326kN	46.6	11.4	1.1	22.2	2.0	31.8	2.9	41.5	5.9	64.4	8.9
575kN	85.5	6.2	0.6	12.1	1.1	17.3	1.6	22.6	3.2	35.1	4.9
932kN	132.9	4.0	0.4	7.8	0.7	11.2	1.0	14.5	2.1	22.6	3.1
RRH-タイプ											
326kN 押	42.2	12.6	1.3	24.5	2.2	35.2	3.2	45.8	6.5	71.1	9.9
213kN 引	26.0	20.5	2.1	39.7	3.5	57.1	5.3	74.4	10.5	115.4	16.0
576kN 押	84.7	6.3	0.6	12.2	1.1	17.5	1.6	22.8	3.2	35.4	4.9
380kN 引	55.4	9.6	1.0	18.7	1.7	26.8	2.5	34.9	4.9	54.2	7.5
931kN 押	152.3	3.5	0.4	6.8	0.6	9.7	0.9	12.7	1.8	19.7	2.7
612kN 引	95.4	5.6	0.6	10.8	1.0	15.5	1.4	20.3	2.9	31.4	4.4
BRD-タイプ											
34.4kN 押	4.91	108.6	10.9	210.5	18.7	—	—	—	—	—	—
16.5kN 引	2.36	226.0	22.6	437.9	38.8	—	—	—	—	—	—
79.4kN 押	11.34	47.0	4.7	91.1	8.1	130.8	12.1	170.5	24.1	—	—
45.0kN 引	6.43	82.9	8.3	160.7	14.3	230.7	21.3	300.7	42.5	—	—
141.9kN 押	20.27	26.3	2.6	51.0	4.5	73.2	6.7	95.4	13.5	148.0	20.6
74.5kN 引	10.65	50.1	5.0	97.0	8.6	139.3	12.8	181.5	25.7	281.7	39.1
221.7kN 押	31.67	16.8	1.7	32.6	2.9	46.8	4.3	61.0	8.6	94.7	13.2
96.1kN 引	13.72	38.9	3.9	75.3	6.7	108.1	10.0	140.9	19.9	218.7	30.4
RR-タイプ											
101kN 押	14.4	37.0	3.7	71.8	6.4	103.0	9.5	134.3	19.0	—	—
33kN 引	4.8	111.1	11.1	215.3	19.1	309.0	28.5	402.8	56.9	—	—
NR-タイプ											
106kN 押	15.2	35.1	3.5	68.0	6.0	97.6	9.0	127.2	18.0	—	—
56kN 引	7.4	72.1	7.2	139.6	12.4	200.5	18.5	261.3	36.9	—	—
218kN 押	31.2	17.1	1.7	33.1	2.9	47.5	4.4	62.0	8.8	96.2	13.4
107kN 引	15.3	34.9	3.5	67.5	6.0	96.9	8.9	126.4	17.9	196.1	27.2
351kN 押	50.2	10.6	1.1	20.6	1.8	29.5	2.7	38.5	5.4	59.8	8.3
185kN 引	26.5	20.1	2.0	39.0	3.5	56.0	5.2	73.0	10.3	113.2	15.7
495kN 押	70.8	7.5	0.8	14.6	1.3	21.0	1.9	27.3	3.9	42.4	5.9
298kN 引	42.6	12.5	1.3	24.3	2.2	34.8	3.2	45.4	6.4	70.4	9.8
1077kN 押	153.9	3.5	0.3	6.7	0.6	9.6	0.9	12.6	1.8	19.5	2.7
581kN 引	83.1	6.4	0.6	12.4	1.1	17.8	1.6	23.3	3.3	36.1	5.0
1496kN 押	213.8	—	—	4.8	0.4	6.9	0.6	9.0	1.3	14.0	1.9
704kN 引	106.7	—	—	9.7	0.9	13.9	1.3	18.1	2.6	28.1	3.9
1984kN 押	283.5	—	—	3.6	0.3	5.2	0.5	6.8	1.0	10.6	1.5
907kN 引	129.6	—	—	8.0	0.7	11.4	1.1	14.9	2.1	23.1	3.2
2907kN 押	415.4	—	—	2.5	0.2	3.6	0.3	4.7	0.7	7.2	1.0
1319kN 引	188.5	—	—	5.5	0.5	7.9	0.7	10.3	1.5	15.9	2.2